



ExionLC™ AD Series

Specifications

The SCIEX ExionLC AD System offers you expandability and robustness for the most challenging method development and sample analysis applications. With a maximum pressure rating of 1300 bar and an autosampler with up to 3 different wash solvents, the system has exceptional chromatographic resolution with virtually undetectable carryover.

ExionLC Controller

ITEM	SPECIFICATION
ENVIRONMENTAL	
Working temperature	4°C to 35°C
Relative humidity	20-85%
Dimensions (w x h x d)	260 x 140 x 420 mm
Weight	5.5 kg
ELECTRICAL	
Power supply voltage	AC100 V to 240 V
Power consumption	Less than 400 VA
Rated breaking capacity	40A
Power supply frequency	50 / 60 Hz
COMMUNICATIONS	
External start input (MAN.INJ.)	1
Error input (IN)	3
General purpose output (OUT)	4
Remote connector	8
Ethernet	1
Optical link (PAC)	1
RS-232C	1
AC remote	1
AC output	2
Interface	SCIEX OS Software 1.x, Analyst® Software 1.7

ExionLC Degasser

ITEM	SPECIFICATION
Type	Membrane based on-line degasser, 5 lines
Volume	Volume approximately 400 µL per line

ExionLC AD Pump

ITEM	SPECIFICATION	
Pump type	Micro volume double plunger pump (approx.. 10 µL/stroke)	
Pumping methods	Constant flow delivery	
Constant flow pumping	Flow rate setting range	0.0001 to 3 mL/min (10-1300 bar) 3.0001 to 5 mL/min (10-800 bar) 5.0001 to 10 mL/min (10-220 bar)
	Flow rate accuracy	±1% (1 mL/min, 800 bar)
	Flow rate precision	RSD <0.06% or 0.02 min. SD, whichever is larger

ExionLC™ AD Pump (continued)

ITEM	SPECIFICATION	
High pressure gradient system	# of solvents mixed	2
	Gradient types	Isocratic, binary, ternary
	Gradient profile	Step and linear gradient at multiple levels
	Maximum # of steps	400
	Mix ratio setting range	0-100% (in 0.1% steps)
	Concentration (composition) accuracy	±0.5% (at 0.5-3 mL/min)
	Flow rates possible	0.0001 to 10 mL / min
	Solvent selection (per pump)	2 with optional solvent selection valve, 4 with optional LPGE unit
Low pressure gradient system	# of solvents mixed	Max. 4 with optional LPGE unit
Pressure limit functions		Upper and lower limits
Liquid contacting part materials		SUS316 L, PEEK, ruby, sapphire, Hastelloy C, polyethylene
Suction filter		10 µm
Line filter		5 µm mesh, capacity 70 µL
Pressure display accuracy		Less than ±2% or ±24 bar, whichever is greater
Plunger rinsing		Automatic piston rinsing function
Leak sensor		Detects leakage from pump
ENVIRONMENTAL		
Working temperature		4°C to 35°C
Relative humidity		20-85%
Dimensions (w x h x d)		260 x 140 x 500 mm
Weight		11.8 kg
ELECTRICAL		
Power supply voltage		AC100 V to 240 V
Power consumption		150 VA
Rated breaking capacity		50A
Power supply frequency		50/60 Hz

ExionLC AD Autosampler

ITEM	SPECIFICATION
Injection method	Variable injection volume flow through design (no sample loss during injection)
Injection volume setting range	0.1 to 50 µL (0.1 to 0.9 µL in 0.1 µL increments, 1 to 50 µL in 1 µL increments)
Samples for processing	<ul style="list-style-type: none"> · With 1.5-2 mL vials: 105 · With 96-well microtiter plate: 192 · With 384-well microtiter plate: 768
Injection volume precision	RSD ≤ 0.25% (at 5 µL injection)
Injection volume accuracy	±1% (50 µL, n = 10) max
Carryover	0.0015% max (under specified conditions)
Sample aspiration rate	0.1 to 15 µL /sec (0.1 µL /sec increments)
Rinse aspiration rate	Variable 1 to 35 µL/sec, (0.1 µL /sec increments)
Rinse solutions	Up to 4 solution types (up to 2 for needle surface, up to 3 for inner surface)
Maximum allowable pressure	1300 bar
Injection cycle time	14 seconds minimum (under specified conditions)
Sample cooling system	Direct cooling system (environment conditions: room temperature below 30°C or lower and humidity 70% or less with cooler set to 4°C), dehumidification function included

ExionLC™ AD Autosampler (continued)

ITEM	SPECIFICATION
Cooling range settings	4 to 40°C (under specified conditions)
Temperature accuracy	±3°C (±6°C for microtiter plates and deep-well plates. Not cooled below 1°C)
Liquid contacting part materials	SUS316 L, SUS316, ceramic, sapphire, PTFE, ETFE, FEP, GFP, PEEK, polyimide
pH range	1-9 standard, 1 to 14 optional
Needle stroke	10 to 54 mm (adjustment range dependent on rack type)
Leak sensor	Automatic leak detection
ENVIRONMENTAL	
Working temperature	4°C to 35°C
Relative humidity	20-85%
Dimensions (w x h x d)	260 x 415 x 500 mm
Weight	33 kg
ELECTRICAL	
Power supply voltage	AC100 V to 240 V
Power consumption	300 VA
Rated breaking capacity	63A
Power supply frequency	50/60 Hz

ExionLC AD Column Oven

ITEM	SPECIFICATION
Heating method	Block heating system
Temperature control range	(Room temperature +5°C) to 150°C
Temperature setting range	4°C to 150°C (in steps of 1°C)
Temperature control precision	±0.05°C (at 25°C)
Column capacity	2 columns at 15 cm max.
ENVIRONMENTAL	
Working temperature	4°C to 35°C
Relative humidity	20-85%
Dimensions (w x h x d)	260 x 210 x 500 mm
Weight	10 kg
ELECTRICAL	
Power supply voltage	AC100 V to 240 V
Power consumption	300 VA
Rated breaking capacity	63A
Power supply frequency	50/60 Hz
SAFETY	
Safety measures	<ul style="list-style-type: none"> • Upper temperature limit can be set to prevent overheating • Equipped with thermal fuses to prevent overheating damage • Equipped with leak sensor for detecting mobile phase leaks

For Research Use Only. Not for use in Diagnostic Procedures.

© 2019 DH Tech. Dev. Pte. Ltd. Trademarks and/or registered trademarks mentioned herein are the property of AB Sciex Pte. Ltd., or their respective owners, in the United States and/or certain other countries. AB SCIEX™ is being used under license.

RUO-MKT-04-2120-B 09/2019



Headquarters
500 Old Connecticut Path, Framingham, MA 01701, USA
Phone 508-383-7800
sciex.com

International Sales
For our office locations please call the division
headquarters or refer to our website at
sciex.com/offices