# SAFETY DATA SHEET



Amplifex Keto Reagent

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: Amplifex Keto Reagent
Product type	: Liquid.
Other means of identification	: Not available.
Product part number	: 4465963
Kit name	: Amplifex Keto Reagent Kit
Kit part number	: 4465962

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use Area of application	: Research and Development : Professional applications.
Uses advised against	
None identified.	

### 1.3 Details of the supplier of the safety data sheet

AB Sciex UK Limited 21F18, 21 Mereside, Alderley Park Macclesfield, Cheshire SK10 4TG United Kingdom Telephone no.: 00800 2255 2279 e-mail address of person : msds.inquiry@sciex.com responsible for this SDS

1.4	Emergency	telephone	number

### National advisory body/Poison Centre

Telephone number	: CHEMTREC: +44 20 3807 3798
<u>Supplier</u>	
Telephone number	: 1-877-740-2129 (8:30A PT - 5:00P PT)

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Product definition : Mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Fam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370

# **SECTION 2: Hazards identification**

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity	<ul> <li>2.5 percent of the mixture consists of component(s) of unknown acute oral toxicity</li> <li>2.5 percent of the mixture consists of component(s) of unknown acute dermal toxicity</li> <li>2.5 percent of the mixture consists of component(s) of unknown acute inhalation</li> <li>toxicity</li> </ul>
Ingredients of unknown	: Contains 2.5% of components with unknown hazards to the aquatic environment

# Ingredients of unknown ecotoxicity

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

# 2.2 Label elements

Hazard pictograms



Signal word Hazard statements		Danger ₱225 - Highly flammable liquid and vapour. H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled. H370 - Causes damage to organs.
Precautionary statements Prevention	:	<ul> <li>280 - Wear protective gloves and protective clothing.</li> <li>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P260 - Do not breathe vapour.</li> </ul>
Response	:	₱308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor. P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Storage	:	Not applicable.
Disposal	:	<b>P</b> 501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	1	methanol
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	;	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Date of issue/Date of revision		: 04/04/2022 Date of previous issue : 02/05/2012 Version : 2 2/15

# Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

Amplifex Keto Reagent

# **SECTION 2: Hazards identification**

Other hazards which do not result in classification

: None known.

# **SECTION 3: Composition/information on ingredients**

### **3.2 Mixtures**

# : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
methanol	EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X	≥90	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

# **SECTION 4: First aid measures**

Ingestion	: Set medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

# 4.2 Most important symptoms and effects, both acute and delayed

# Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

# 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>
Specific treatments	: No specific treatment.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media Suitable extinguishing media	: Use	e dry che	emical, CO <sub>2</sub> , water sp	ray (fog) or foam.			
Unsuitable extinguishing media	: Do	not use v	water jet.				
5.2 Special hazards arising f	rom the	substa	nce or mixture				
Hazards from the substance or mixture	haz	ard. In a		our. Runoff to sewer ma ressure increase will oc ent explosion.			
Hazardous thermal decomposition products	car car nitr	bon diox bon mon ogen oxi	ide noxide	lude the following mater	ials:		
5.3 Advice for firefighters Special protective actions for fire-fighters	the trai	re is a fir ning. Mo	re. No action shall be	moving all persons from taken involving any per ire area if this can be do iners cool.	sonal risk or wi	thout su	uitable
Date of issue/Date of revision	: 04	4/04/2022	Date of previous issu	: 02/05/2012	Version	:2	4/15

# **SECTION 5: Firefighting measures**

<ul> <li>Special protective equipment for fire-fighters</li> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.</li> </ul>	Special protective equipment for fire-fighters
---	---

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	containment and cleaning up

# al for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
---------------------	---

# **SECTION 7: Handling and storage**

Advice on general	: Eating, drinking and smoking should be prohibited in areas where this material is
occupational hygiene	handled, stored and processed. Workers should wash hands and face before eating,
	drinking and smoking. Remove contaminated clothing and protective equipment
	before entering eating areas. See also Section 8 for additional information on
	hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds (in tonnes)

### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
H2	50 tonne	200 tonne
H3	50 tonne	200 tonne
P5c	5000 tonne	50000 tonne

### 7.3 Specific end use(s)

Recommendations: Not available.Industrial sector specific: Not available.solutions: Not available.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational exposure limits**

Product/ingredient name	Exposure limit values	
Methanol	<ul> <li>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</li> <li>STEL: 333 mg/m<sup>3</sup> 15 minutes.</li> <li>STEL: 250 ppm 15 minutes.</li> <li>TWA: 266 mg/m<sup>3</sup> 8 hours.</li> <li>TWA: 200 ppm 8 hours.</li> <li>EU OEL (Europe, 10/2019). Absorbed through skin. Notes: list of indicative occupational exposure limit values</li> <li>TWA: 200 ppm 8 hours.</li> <li>TWA: 200 ppm 8 hours.</li> <li>TWA: 200 ppm 8 hours.</li> </ul>	
procedures atmosphere or of the ventilation protective equination the following: In the assessment limit values and atmospheres - exposure to ch	contains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectiveness on or other control measures and/or the necessity to use respiratory pment. Reference should be made to monitoring standards, such as European Standard EN 689 (Workplace atmospheres - Guidance for at of exposure by inhalation to chemical agents for comparison with d measurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment of emical and biological agents) European Standard EN 482 nospheres - General requirements for the performance of procedures	

# **SECTION 8: Exposure controls/personal protection**

for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
methanol	DNEL	Short term Dermal	8 mg/kg	General	Systemic
	DNEL	Long term Dermal	bw/day 8 mg/kg bw/day	population General population	Systemic
	DNEL	Short term Dermal	40 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	40 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	50 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	50 mg/m³	General population	Local
	DNEL	Short term Inhalation	50 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	50 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	260 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	260 mg/m <sup>3</sup>	Workers	Systemic

# **PNECs**

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection measure	<u>s</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	

# **SECTION 8: Exposure controls/personal protection**

•	· · ·
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: 🗭 olourless.
Odour	: Not available.
Odour threshold	: Not available.
рН	: 8.5
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: >36°C
Flash point	: Closed cup: <23°C
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not applicable.
Upper/lower flammability or explosive limits	: Not available.
Vapour pressure	: Not available.
Vapour density	: Not available.
Relative density	: Not available.
Solubility(ies)	: Not available.
Partition coefficient: n-octanol/ water	: Not applicable.
Auto-ignition temperature	: Not available.
Date of issue/Date of revision	: 04/04/2022 Date of previous issue

:02/05/2012

# SECTION 9: Physical and chemical properties Decomposition temperature : Not available. Viscosity : Not available. Explosive properties : Not available. Oxidising properties : Not available. 9.2 Other information Physical/chemical properties Physical/chemical properties : No additional information. Comments : No additional information.

# **SECTION 10: Stability and reactivity**

10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	:	Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
10.5 Incompatible materials	:	Reactive or incompatible with the following materials: oxidising materials Reactive or incompatible with the following materials: metals.
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

# Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
methanol	LC50 Inhalation Vapour	Rat	189.95 mg/l	1 hours
	LC50 Inhalation Vapour	Rat	145000 ppm	1 hours
	LC50 Inhalation Vapour	Rat	83.84 mg/l	4 hours
	LC50 Inhalation Vapour	Rat	64000 ppm	4 hours
	LD50 Dermal	Rabbit	15800 mg/kg	-
	LD50 Oral	Rat	5600 mg/kg	-

**Conclusion/Summary** : Not available.

# Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Amplifex Keto Reagent methanol	102.5	307.6	N/A	3.1	N/A
	100	300	N/A	3	N/A

# **SECTION 11: Toxicological information**

Irritation/Corrosion		
<b>Conclusion/Summary</b>	:	Not available.
<u>Sensitisation</u>		
<b>Conclusion/Summary</b>	:	Not available.
<b>Mutagenicity</b>		
<b>Conclusion/Summary</b>	:	Not available.
<b>Carcinogenicity</b>		
<b>Conclusion/Summary</b>	:	Not available.
Reproductive toxicity		
<b>Conclusion/Summary</b>	:	Not available.
<b>Teratogenicity</b>		
Conclusion/Summary	:	Not available.
Specific target organ toxicity	<u>ر (</u>	<u>single exposure)</u>

	Product/ingredient name	Category	Route of exposure	Target organs
met	nanol	Category 1	-	-

# Specific target organ toxicity (repeated exposure)

Not available.

### **Aspiration hazard**

Not available.

Information on likely routes of exposure	1	Routes of entry anticipated: Oral, Dermal, Inhalation.
Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	Foxic if inhaled. Causes damage to organs following a single exposure if inhaled.
Skin contact	:	✓ oxic in contact with skin. Causes damage to organs following a single exposure in contact with skin.
Ingestion	1	roxic if swallowed. Causes damage to organs following a single exposure if swallowed.
Symptoms related to the phy	<u>sic</u>	al, chemical and toxicological characteristics
Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.
<u>Delayed and immediate effec</u> <u>Short term exposure</u>	<u>ts</u>	as well as chronic effects from short and long-term exposure
Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Long term exposure		

SECTION 11: Toxicological information		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Potential chronic health eff	ects	
General	: No known significant effects or critical hazards.	
Carcinogenicity	: No known significant effects or critical hazards.	
Mutagenicity	: No known significant effects or critical hazards.	
Reproductive toxicity	: No known significant effects or critical hazards.	
Other information	: Not available.	

# **SECTION 12: Ecological information**

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
methanol	Acute EC50 16.912 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute LC50 2500000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 3289 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 290 mg/l Fresh water	Fish - Danio rerio - Egg	96 hours
	Chronic NOEC 9.96 mg/l Marine water	Algae - Ulva pertusa	96 hours
Conclusion/Summary	: Not available.	·	•

# 12.2 Persistence and degradability

12.2 Persistence and degra	luability
Conclusion/Summary	<ul> <li>Not available</li> </ul>

oonerasion/ourninary			
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
methanol	-	-	Readily

### **12.3 Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
methanol	-0.77	<10	low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	UN1230	UN1230	UN1230	UN1230
14.2 UN proper shipping name	METHANOL solution	METHANOL solution	METHANOL solution	Methanol solution
14.3 Transport hazard class(es)	3 (6.1)	3 (6.1)	3 (6.1)	3 (6.1)
14.4 Packing group	II	11	11	11
14.5 Environmental hazards	No.	Yes.	No.	No.
Additional information ADR/RID : Mazard identification number 336 Limited quantity 1 L Special provisions 279 Tunnel code (D/E)				
ADN	<ul> <li>The product is only regulated as an environmentally hazardous substance when transported in tank vessels.</li> <li>Special provisions 279, 802</li> </ul>			
IMDG		<u>y schedules</u> F-E, S-D <u>ovisions</u> 279		

# **SECTION 14: Transport information**

ΙΑΤΑ	<ul> <li>Quantity limitation Passenger and Cargo Aircraft: 1 L. Packaging instructions: 352. Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities - Passenger Aircraft: 1 L. Packaging instructions: Y341.</li> <li>Special provisions A113</li> </ul>
14.6 Special precautions for user	: <b>Fransport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport in bulk according to IMO instruments	: Not available.
SECTION 15: Regulat	tory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

### Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Ingredient name	EC number	CAS number	Restriction
methanol	200-659-6	67-56-1	69

Substances requiring : N

labelling

: Not applicable.

### **Other EU regulations**

**Europe inventory** : Not determined.

Ozone depleting substances (1005/2009/EU)

Not listed.

### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

### Seveso Directive

This product is controlled under the Seveso Directive.

### Danger criteria

Category			
<mark>⊮</mark> 2			
₩2 H3 P5c			
P5c			

### International regulations

### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

### Montreal Protocol

Date of issue/Date of revision

SECTION 15: Regulatory information		
Not listed.		
Stockholm Convention of Not listed.	on Persistent Organic Pollutants	
Rotterdam Convention of Not listed.	on Prior Informed Consent (PIC)	
UNECE Aarhus Protocol Not listed.	on POPs and Heavy Metals	
15.2 Chemical safety assessment	<ul> <li>This product contains substances for which Chemical Safety Assessments are still required.</li> </ul>	

- required.
- 15.3 Registration status
- : Mixture. Information concerning the substance : Contact local supplier or distributor.

# **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative
Key literature references and sources for data	Regulation (EC) No. 1272/2008 [CLP]; European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), concluded in Geneva on 30 September 1957 plus amendments (Uniform text: Journal of Laws 27/2009 pos. 162 plus amendments); European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (ADN); Occupational exposure limits; International regulations

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
<b>F</b> am. Liq. 2, H225	On basis of test data
Acute Tox. 3, H301	Calculation method
Acute Tox. 3, H311	Calculation method
Acute Tox. 3, H331	Calculation method
STOT SE 1, H370	Calculation method

### Full text of abbreviated H statements

<b>₩</b> 225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.

Full text of classifications [CLP/GHS]

# **SECTION 16: Other information**

Acute Tox. 3 Flam. Liq. 2 STOT SE 1	ACUTE TOXICITY - Category 3 FLAMMABLE LIQUIDS - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1
Training advice	: Ensure operatives are trained to minimise exposures. Training staff on good practice.
Date of issue/ Date of revision	: 04/04/2022
Date of previous issue	: 02/05/2012
Version	: 2
Notice to reader	

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.