# SAFETY DATA SHEET



APCI Negative Calibration Solution for the SCIEX X500 System

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: APCI Negative Calibration Solution for the SCIEX X500 System
Product type	: Liquid.
Other means of identification	: Not available.
Product part number	: 5042915
1.2 Relevant identified us	es of the substance or mixture and uses advised against
Product use	: Research and Development
Area of application	: Professional applications.
Uses advised against	
None identified.	

### 1.3 Details of the supplier of the safety data sheet

AB Sciex UK Limited 21F18, 21 Mereside, Alderley Park Macclesfield, Cheshire SK10 4TG United Kingdom Telephone no.: 00800 2255 2279

e-mail address of person : msds.inquiry@sciex.com responsible for this SDS

### 1.4 Emergency telephone number

National advisory body/Poison Centre		
Telephone number	: CHEMTREC: +44 20 3807 3798	
<u>Supplier</u>		
Telephone number	: 1-877-740-2129 (8:30A PT - 5:00P PT)	

## **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Product definition

: Mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Mam. Liq. 2, H225 Acute Tox. 4, H302

Eye Irrit. 2, H319

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

APCI Negative Calibration Solution for the SCIEX X500 System

### **SECTION 2: Hazards identification**

2.2 Label elements

#### **Hazard pictograms** Signal word : Danger **Hazard statements** : H225 - Highly flammable liquid and vapour. H302 - Harmful if swallowed. H319 - Causes serious eye irritation. **Precautionary statements Prevention** : P280 - Wear eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P270 - Do not eat, drink or smoke when using this product. P264 - Wash thoroughly after handling. : P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Response Remove contact lenses, if present and easy to do. Continue rinsing. **Storage** : Not applicable. : **P**501 - Dispose of contents and container in accordance with all local, regional, **Disposal** national and international regulations. **Hazardous ingredients** : acetonitrile Supplemental label : Not applicable. elements **Annex XVII - Restrictions** : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Special packaging requirements **Containers to be fitted** : Not applicable. with child-resistant fastenings Tactile warning of danger : Not applicable. 2.3 Other hazards **Product meets the criteria** : This mixture does not contain any substances that are assessed to be a PBT or a for PBT or vPvB according vPvB. to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do : None known.

not result in classification

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures :	Mixture			
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
zcetonitrile	EC: 200-835-2 CAS: 75-05-8 Index: 608-001-00-3	≥25 - ≤50	Flam. Liq. 2, H225 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Eye Irrit. 2, H319	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

- Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

4.1 Description of first aid n	neasures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	<ul> <li>Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.</li> </ul>
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
Date of issue/Date of revision	: 25/02/2022 Date of previous issue : 14/09/2015 Version : 2 3/15

### **SECTION 4: First aid measures**

### 4.2 Most important symptoms and effects, both acute and delayed

#### **Over-exposure signs/symptoms**

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	If ighly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides Cyanides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

APCI Negative Calibration Solution for the SCIEX X500 System

### **SECTION 7: Handling and storage**

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Seveso Directive - Reporting thresholds (in tonnes)

### Danger criteria

	Notification and MAPP threshold	Safety report threshold
₽5c	5000 tonne	50000 tonne

### 7.3 Specific end use(s)

#### Recommendations

: Not available. : Not available.

# Industrial sector specific solutions

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational exposure limits**

Product/ingredient na	Exposure limit values	
cetonitrile	<ul> <li>EH40/2005 WELs (United Kingdom (UK), 1/2020).</li> <li>STEL: 102 mg/m<sup>3</sup> 15 minutes.</li> <li>STEL: 60 ppm 15 minutes.</li> <li>TWA: 40 ppm 8 hours.</li> <li>TWA: 68 mg/m<sup>3</sup> 8 hours.</li> <li>EU OEL (Europe, 10/2019). Absorbed through skin. Notes: list of indicative occupational exposure limit values</li> <li>TWA: 40 ppm 8 hours.</li> <li>TWA: 40 ppm 8 hours.</li> <li>TWA: 70 mg/m<sup>3</sup> 8 hours.</li> </ul>	
procedures a c p t t t t t t t t t t t t t t t t t t		
DNELs/DMELs		

## **SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
acetonitrile	DNEL	Short term Oral	0.6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	4.8 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	4.8 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	22 mg/m³	General	Local
	DNEL	Long term Dermal	32.2 mg/ kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	68 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	68 mg/m³	Workers	Local
	DNEL	Short term Inhalation	68 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	68 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	220 mg/m <sup>3</sup>	General population	Systemic

### **PNECs**

No PNECs available

### 8.2 Exposure controls

Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection measur	es	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

### **SECTION 8: Exposure controls/personal protection**

Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties						
<u>Appearance</u>						
Physical state	: Liquid.					
Colour	: 🗭 olourless.					
Odour	: Not available.					
Odour threshold	: Not available.					
рН	: 4					
Melting point/freezing point	: Not available.					
Initial boiling point and boiling range	: >36°C					
Flash point	: Closed cup: <23°C					
Evaporation rate	: Not available.					
Flammability (solid, gas)	: Not applicable.					
Upper/lower flammability or explosive limits	: Not available.					
Vapour pressure	: Not available.					
Vapour density	: Not available.					
Relative density	: Not available.					
Solubility(ies)	: Not available.					
Partition coefficient: n-octanol/ water	: Not applicable.					
Auto-ignition temperature	: Not available.					
Decomposition temperature	: Not available.					
Viscosity	: Not available.					
Explosive properties	: Not available.					
Oxidising properties	: Not available.					

APCI Negative Calibration Solution for the SCIEX X500 System

# **SECTION 9: Physical and chemical properties**

### 9.2 Other information

Physical/chemical properties : No additional information. comments

# SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidising materials
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

### **11.1 Information on toxicological effects**

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
zcetonitrile	LC50 Inhalation Gas.	Rat	17100 ppm	4 hours
	LD50 Oral	Rat	2460 mg/kg	-

**Conclusion/Summary** : Not available.

### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
APCI Negative Calibration Solution for the SCIEX X500 System acetonitrile	1137.7 500	2502.9 1100	38908 17100	N/A N/A	N/A N/A

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
cetonitrile	Eyes - Moderate irritant	Rabbit	-	24 hours 100 uL	-
Conclusion/Summary <u>Sensitisation</u>	: Not available.				
Conclusion/Summary	: Not available.				

# **SECTION 11: Toxicological information**

	5		
Mutagenicity			
Conclusion/Summary	: Not available.		
<b>Carcinogenicity</b>			
Conclusion/Summary	: Not available.		
Reproductive toxicity			
Conclusion/Summary	: Not available.		
<u>Teratogenicity</u>			
Conclusion/Summary	: Not available.		
Specific target organ toxicit	<u>y (single exposure)</u>		
Not available.			
Specific target organ toxicit	<u>y (repeated exposure)</u>		
Not available.			
Aspiration hazard			
Not available.			
Information on likely routes	: Routes of entry anticipated: Oral, Dermal, Inhalation.		
of exposure	r Rouce er entry anticipated. eral, Dermal, innalation.		
Potential acute health effects			
Eye contact	: Causes serious eye irritation.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: Harmful if swallowed.		
	sical, chemical and toxicological characteristics		
Eye contact	: Adverse symptoms may include the following: pain or irritation		
	watering		
	redness		
Inhalation	: No specific data.		
Skin contact	: No specific data.		
Ingestion	: No specific data.		
Deleved and immediate offer	te es well es almentis effects from allent and lange terms avec		
	<u>ts as well as chronic effects from short and long-term exposure</u>		
Short term exposure Potential immediate	: Not available.		
effects	. Not available.		
Potential delayed effects	: Not available.		
Long term exposure			
Potential immediate	: Not available.		
effects			
Potential delayed effects	: Not available.		
Potential chronic health effe	ects		
General	: No known significant effects or critical hazards.		
Carcinogenicity	: No known significant effects or critical hazards.		
Date of issue/Date of revision	: 25/02/2022 Date of previous issue : 14/09/2015 Vers	ion	:2

10/15

APCI Negative Calibration Solution for the SCIEX X500 System

### **SECTION 11: Toxicological information**

Mutagenicity

: No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

### Other information

: Not available.

### **SECTION 12: Ecological information**

### **12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
acetonitrile	Acute IC50 3685000 µg/l Fresh water Acute LC50 3600000 µg/l Fresh water Acute LC50 1000000 µg/l Fresh water Chronic NOEC 1000000 µg/l Fresh water Chronic NOEC 160000 µg/l Fresh water	Aquatic plants - Lemna minor Daphnia - Daphnia magna Fish - Pimephales promelas Aquatic plants - Lemna minor Daphnia - Daphnia magna	96 hours 48 hours 96 hours 96 hours 21 days

### **12.2 Persistence and degradability**

Product/ingredient name	Test	Result	Dose	Inoculum
zcetonitrile	OECD 301C Ready Biodegradability - Modified MITI Test (I)	65 % - Readily - 28 days	-	Activated sludge
Conclusion/Summary	: Not available.	•		

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
acetonitrile	-	-	Readily

#### **12.3 Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
acetonitrile	-0.34	-	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)	:	Not available.
Mobility	:	Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

### **13.1 Waste treatment methods**

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	UN1648	UN1648	UN1648	UN1648
14.2 UN proper shipping name	ACETONITRILE solution	ACETONITRILE solution	ACETONITRILE solution	Acetonitrile solution
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	11	11	II	II
14.5 Environmental hazards	No.	No.	No.	No.
Additional informati ADR/RID	: Hazard ic	lentification number 33 Juantity 1 L	3	

IMDG

ΙΑΤΑ

- Tunnel code (D/E) : Emergency schedules F-E, S-D
- : Quantity limitation Passenger and Cargo Aircraft: 5 L. Packaging instructions: 353. Cargo Aircraft Only: 60 L. Packaging instructions: 364. Limited Quantities -
  - Passenger Aircraft: 1 L. Packaging instructions: Y341.

APCI Negative Calibration Solution for the SCIEX X500 System

### **SECTION 14: Transport information**

14.6 Special precautions for	:	Transport within user's premises: always transport in closed containers that are
user		upright and secure. Ensure that persons transporting the product know what to do in
		the event of an accident or spillage.

14.7 Transport in bulk: Not available.according to IMOinstruments

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

### Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous

substances, mixtures and articles

Substances requiring : Not applicable. labelling

#### **Other EU regulations**

Europe inventory	: Not determined.
Industrial emissions (integrated pollution prevention and control) - Air	: Listed
Industrial emissions (integrated pollution prevention and control) - Water	: Listed
Ozone depleting substanc	<u>es (1005/2009/EU)</u>
Not listed.	

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

### Seveso Directive

This product is controlled under the Seveso Directive.

Dan	qer	crite	eria
	· · ·		

Category

P5c

### International regulations

### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

SECTION 15: Regulatory	information
------------------------	-------------

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

15.2 Chemical safety	1	This product contains substances for which Chemical Safety Assessments are still
assessment		required.
15.3 Registration status	:	Mixture. Information concerning the substance : Contact local supplier or distributor.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative
Key literature references and sources for data	: Regulation (EC) No. 1272/2008 [CLP]; European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), concluded in Geneva on 30 September 1957 plus amendments (Uniform text: Journal of Laws 27/2009 pos. 162 plus amendments); European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (ADN); Occupational exposure limits; International regulations

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 2, H225	On basis of test data
Acute Tox. 4, H302	Calculation method
Eye Irrit. 2, H319	Calculation method

#### Full text of abbreviated H statements

### Full text of classifications [CLP/GHS]

Cute Tox. 4	ACUTE TOXICITY - Category 4
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2

Training advice

: Ensure operatives are trained to minimise exposures. Training staff on good practice.

SECTION	16:	Other	information
---------	-----	-------	-------------

Date of issue/ Date of revision	: 25/02/2022
Date of previous issue	: 14/09/2015
Version	: 2

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.